

PRODUCT INFORMATION

Norm	EN 14904			
Intensity of use	ISO 10874 (EN 685)		23 domestic heavy 34 commercial very heavy 43 industrial heavy	class
Total thickness	EN ISO 24346 (EN 428)		6,80	mm
Wear layer	EN ISO 24340 (EN 429)		0,65	mm
Abrasion group	EN 660-2		T	class
Total weight	EN ISO 23997 (EN 430)		4200	g/m ²
Standard width	EN ISO 24341 (EN 426)		2	m
Standard length	EN ISO 24341 (EN 426)		+/- 18	m

TECHNICAL INFORMATION

Dimensional stability	EN ISO 23999 (EN 434)		≤ 0,40	%
Light stability	EN ISO 105 B02		≥ 6	degree
Dynamic coefficient of friction	EN 13893		> 0,60	
Reaction to fire Report number ---- VNL F 031380.4	EN 13501-1		Cfl-s1 (glued on concrete)	class
Chemical resistance	ISO 26987 (EN 423)		resistant	
Vertical ball behavior	EN 12235		> 90	%
Friction	EN 13036-4		95	units
Shock absorption	EN 14808		28	%
Vertical deformation	EN 14809		0,80	mm
Abrasion resistance	EN ISO 5470-1		85,4	mg
Content of pentachlorophenol	EN 12673		< 5	ppm
Resistance of indentation	EN 1516		< 0,50	mm

Please note that the data given could be imprecise and liable to modifications of a technical nature at any time. The information in these documents is valid from 22/05/2024, and Beauflor reserves the right to make changes at any moment and without prior notice. Our technology is constantly evolving, so before carrying out any projects we encourage you to contact us to maintain our highest level of standards.

SUSTAINABILITY

We feel that it's our moral duty to contribute to a more sustainable world. This is illustrative by the choice of raw materials, of partners, of transport and of fabrication processes. Our selection of core materials is based on a combination of our clients' requirements for a quality product as well as requirements for a minimal impact on the environment.

Ortho-phthalates free

100% Recyclable

- No heavy metals
- No solvents
- No formaldehyde
- No harmful plasticizers

E1
APPROVED FOR EMISSIONS

Level of formaldehyde is inferior to 0.1ppm (= 0.12 mg/m³ of air)

MISSIONS DANS L'AIR INTÉRIEUR

A+

Our products are classified as A+ for the emission of volatile substances in inside air (compulsive sanitary labelling in France since January 2012)

floor score

A+

Approved for emissions

BB

Auszeichnung für gesundheitlichen Bewertung von Bauprodukten

Certifié ISO 14001

Slovenian plant

Certifié ISO 9001

Slovenian/Belgian plant

FEATURES

EN 14904:2006

CE

20

DOP: 641-SF0020-1

Juška d.o.o.
Ljubljana, 2010 Zlatič
SLOVENIA

Internal use as sports flooring coverings

Friction conforms
Resistance to wear conforms
Reaction to the fire Cfl-s1
Shock absorption P1
Emission to formaldehyde E1
Content of Pentachlorophenol < 5 ppm